

APPLICATIONS:

Indoor Outdoor Natural Gas LP (Liquid Propane) Unvented Multi-Sided Availability Combustible Floor Installation Custom Finish

A gas fireplace blends seamlessly into your home's footprint, with Isokern's **Vent-Free Series**.

The Vent-Free series offers a variety of opening heights and is fully customizable to fit in with any design plan. With its large finished openings and see-thru availability, the Vent-Free Series is a perfect heating solution for any multi-family home, new home, remodeling project or outdoor concept.

Specifications

Please Note: Zero clearance to combustible material. Combustible framing at bottom, top, sides, and rear.

Combustible sheathing and trim must be kept a minimum of 12" from the top of opening, and a minimum of 8" to the sides.

Combustible mantels must be installed per installation manual. The projection into the room dictates minimum distance above opening.

Front View



Side View

Plan View







	Model	В	С	D	E	F	G
Ş	36	37 1/2"	31 1/2"	27 1/4"	37 1/8″	43″	10 1/2"
View	42	37 1/2"	31 1/2"	33 1/4"	43 1/8″	49″	10 1/2"
t	46	37 1/2"	31 1/2"	37 1/4"	47 1/8″	53"	10 1/2"
Front	60	40 1/2"	31 1/2"	57 3/4"	67 1/2″	73 1/2″	10 1/2″
	72	41 1/2"	31 1/2"	70 1/8″	80″	85 7/8″	11 1/2″

	Model	В	С	Н	J	Μ
View	36	37 1/2"	31 1/2"	25 1/4"	34 1/2"	5″
	42	37 1/2"	31 1/2"	25 1/4"	34 1/2"	5″
	46	37 1/2"	31 1/2"	25 1/4"	34 1/2"	5″
Side	60	40 1/2"	31 1/2"	25 1/4"	34 1/2"	5″
	72	41 1/2"	31 1/2"	26 1/4"	35 1/2"	6″

Plan View	Model	D	E	F	S	Т
	36	27 1/4″	37 1/8"	43″	25 1/4"	20 1/4"
	42	33 1/4"	43 1/8″	49″	25 1/4"	20 1/4"
	46	37 1/4"	47 1/8″	53″	25 1/4"	20 1/4"
	60	57 3/4"	67 1/2"	73 1/2″	25 1/4"	20 1/4"
	72	70 1/8″	80″	85 7/8″	26 1/4"	21 1/4"