



ISO KERN[®] MAXIMUS[®] *Linear*

OPEN FRONT | GLASS FRONT
**Product Details
& Specifications**





Maximus Linear Model Sizes: 48" • 60" • 72" • 96" • 120"

APPLICATIONS:

Indoor | Outdoor
 (NG) Natural Gas
 (LP) Liquid Propane
 Custom Finish
 Combustible Floor Installation
 Zero Clearance to Open Front
 12" B-Vent Chimney System
 Isoflames Linear Burner
 Glass Media
 Electronic Ignition System
 Mechanical Exhaust Fan


The Maximus Linear Open-Front or Glass-Front Series
The same trusted pumice—with a sleek,
bold design.

The Maximus Linear Series is a sophisticated fireplace system that blends cutting-edge utility with refined style. Each unit is sold with a **Remote-Controlled Electronic Ignition System** and the **X-Ventiso Meridian Mechanical Fan**, delivering ultimate performance and convenience.

Choose between an **open-front** or **glass-front** firebox, then finish your look with **colored glass media** or a **driftwood log set**. The glass-front model operates without drawing conditioned air from the room, ensuring compliance with air quality control standards.


Open Front - 48, 60, 72, 96 & 120

Please Note: This unit utilizes a single 12" BVent Chimney that can be terminated vertically or horizontally. All units are power vented. Zero Clearance to glass front. Models 72, 96 & 120 requires 6" x 6" x 1/2" Steel Angle cut to span firebox opening. This item is not included in the components and can be sourced locally.



Framing & Weight

Model	Minimum Framing	Weight
48	56"W x 51"H x 29 1/2"D	1275 lbs
60	77"W x 51"H x 29 1/2"D	1720 lbs
72	89"W x 51"H x 29 1/2"D	1990 lbs
96	112"W x 51"H x 29 1/2"D	2450 lbs
120	135"W x 51"H x 29 1/2"D	2997 lbs



Front View	Model	A	B	C	E	F	L
	48	43"	51"	18 7/8"	48"	52 3/4"	8"
	60	63 3/16"	51"	18 7/8"	78 1/4"	73 7/16"	8"
	72	76"	51"	18 7/8"	81 1/4"	85 13/16"	8"
	96	98 1/8"	51"	18 7/8"	103 5/8"	109"	8"
	120	121 5/8"	51"	18 7/8"	127 1/8"	132"	8"


Side View	Model	B	C	H	I	J	M
	48	51"	18 7/8"	25 1/4"	20 5/8"	29 3/4"	5"
	60	51"	18 7/8"	25 1/4"	20 5/8"	29 3/4"	5"
	72	51"	18 7/8"	25 1/4"	20 5/8"	29 3/4"	5"
	96	51"	18 7/8"	25 1/4"	20 5/8"	29 3/4"	5"
	120	51"	18 7/8"	25 1/4"	20 5/8"	29 3/4"	5"

Plan View	Model	D	E	F	S	T
	48	34 11/16"	48"	52 3/4"	28"	25 3/16"
	60	57 11/16"	65 3/4"	73 7/16"	28"	25 3/16"
	72	67 11/16"	81 1/4"	85 13/16"	28"	25 3/16"
	96	89 11/16"	103 5/8"	109"	28"	25 3/16"
	120	116 11/16"	127 1/8"	132"	28"	25 3/16"

Glass Front - 48, 60, 72, 96 & 120

Please Note: Zero Clearance to glass front. Models 72, 96 & 120 requires 6" x 6" x 1/2" Steel Angle cut to span firebox opening. This item is not included in the components and can be sourced locally.

Steel Angle: 6" x 6" x 1/2" cut to span firebox opening on models **72, 96 & 120**. This item is not included in the components and can be sourced locally.



Framing & Weight

Model	Minimum Framing	Weight
48	56"W x 64 1/2"H x 29 1/2"D	1652 lbs
60	77"W x 64 1/2"H x 29 1/2"D	2204 lbs
72	89"W x 64 1/2"H x 29 1/2"D	2578 lbs
96	112"W x 64 1/2"H x 29 1/2"D	3132 lbs
120	135"W x 64 1/2"H x 29 1/2"D	3844 lbs

Front View

Model	A	B	C	E	F	L
48	43"	62 7/8"	18 7/8"	48 1/4"	53"	8"
60	63 3/16"	62 7/8"	18 7/8"	78 1/4"	73 7/16"	8"
72	76"	62 7/8"	18 7/8"	81 1/4"	85 13/16"	8"
96	99 1/4"	62 7/8"	18 7/8"	130 5/8"	109"	8"
120	122 1/4"	62 7/8"	18 7/8"	127 1/8"	132"	8"

Side View

Model	B	C	H	I	J	M
48	62 7/8"	18 7/8"	25 1/4"	20 5/8"	42 1/8"	5"
60	62 7/8"	18 7/8"	25 1/4"	20 5/8"	42 1/8"	5"
72	62 7/8"	18 7/8"	25 1/4"	20 5/8"	42 1/8"	5"
96	62 7/8"	18 7/8"	25 1/4"	20 5/8"	42 1/8"	5"
120	62 7/8"	18 7/8"	25 1/4"	20 5/8"	42 1/8"	5"

Plan View

Model	D	E	F	S	T
48	34 11/16"	48 1/2"	53"	28"	23"
60	57 11/16"	78 1/4"	73 7/16"	28"	23"
72	70 11/16"	81 1/4"	85 13/16"	28"	23"
96	92 1/2"	103 5/8"	109"	28"	23"
120	116"	127 1/8"	132"	28"	23"